



Heavy Cut H9.02

Coarse polishing compound, silicone-oil-free

page 1 of 1

Innovative machine polish for fast reworking of heavily weathered paintwork, elimination of deep scratches, and effective removal of paint mists and sanding traces of up to 1,200 grain. With its extremely homogeneous abrasive grain, Heavy Cut 9.02 achieves an extremely high level of cut with an excellent gloss level. Can be polished for prolonged periods without sticking and with low dust formation. Ideally suited to all types of paint (both soft and scratch-proof).

Abrasion level: 9,0 Gloss level: 6,0

Areas of use

Paint on cars, commercial vehicles, motorcycles, etc.

Recommendations for use

Apply in a crosswise motion with a rotary polisher and a lambskin pad (for sanding traces of 1,200–2,500) or the Heavy Cut Pad (for sanding traces of 1,500–3,000). Apply polishing compound at medium speed and with medium pressure. Polish afterwards with Micro Cut M3.02 or Micro Cut & Finish P3.01 for the best possible finish.

Container

Container	Item no.
1 L	458001
0,25 L	458250

Warnings

Shake before using. Before using, check suitability and compatibility. Do not use on hot surfaces. Safety data sheet available on request for trade users. Protect against frost and excessive heat.

Notice

This product information can advise you only without obligation. Liability on our part can not be derived. Please check whether the product is suitable for your application. We will be pleased to assist you.