



Schleifpaste H7.01

Coarse polishing compound, silicone-oil-free

Schleifpaste H7.01 is the heavily abrasive machine polish for quick reconditioning of heavily weathered paintwork, removing paint overspray and sanding traces to P2000 grain. Cut: 7,5. Gloss: 3,0

page 1 of 1

Areas of use

Paintwork of cars, commercial vehicles, motor cycles, etc.

Recommendations for use

Apply Schleifpaste to the polishing pad (hard white polishing pad or medium hard yellow polishing pad) and polish the precleaned surface crosswise with max. 2.000 rpm. The abrasivity/grinding performance can be varied with pressure, polishing pad and speed. At the start of the polishing process we recommend applying greater pressure at a lower speed. Then gradually reduce the pressure and finish off at a higher speed. Polish residues can be removed easily with our ultrasound cut Profi microfibre cloth. Streaks or traces of polish are removed with our Hochglanz-Antihologramm-Politur.

Container

Container	Item no.
1 L	180001
0,25 L	180250

Warnings

Shake before using.;Not suitable for scratch-resistant paint.;Protect against frost and excessive heat.;Before using, check suitability and compatibility.;Do not use on hot surfaces.;

Notice

This product information can advice you only without obligation. Liability on our part can not be derived.Please check whether the product is suitable for your application. We will be pleased to assist you.